

# APstorage Battery

---

- CATL LFP Cells Inside
- Supports Charging Down to -5°C
- Automatic Parallel Configuration
- Outdoor and Indoor Application (IP65)



## Features

1. Easy installation
2. Slim & modern design
3. Advanced BMS control
4. Parallel capacity up to 160 kWh
5. Black out and emergency back-up
6. Self-heating for low ambient temperatures (optional)
7. Remote monitoring with over-the-air updates(optional)

# Datasheet | APbattery-51.2V/10.24kWh-U

**Model**

**APbattery-51.2V/10.24kWh-U**

**Region**

**NA**

## General Specifications

Rated Capacity	200Ah
Rated voltage	51.2V
Rated Energy	10.24 kWh
Max.Parallel Quantity	16 Sets in Parallel, 163.84 kWh
Rated Charging / Discharging Current	0.6C, 120A
Max.Discharge Continuous Current	0.6C, 120A
Battery Max.Charge / Discharge Powe	6.14kW/6.14kW
Peak Discharge Current Power	160A/8.19kW, 1min.
Available SOC Range	0%-100% 90% DOD is recommended
Dimensions	Width: 550 (±5) mm / 21.7 in, Depth: 165 (+5) mm / 6.50 in, Height: 1000 (±5) mm / 39.4 in
Weight	- 213.8 lbs
Operating Temperature <sup>(1)</sup>	Charging Temperature: 23°F - 131°F Discharge Temperature : 5°F - 131°F
Storage Temperature <sup>(2)</sup>	5°F - 131°F
Working Humidity	5-95% RH (Non-Condensing)
Altitude	≤ 6561ft
Communication	CAN / RS485 / Dry Contact / WiFi (WiFi Stick Optional)
Certification	UL9540A, UL1973, UN38.3
Cycle Life	6000 Cycles
Designed Calendar Life	15 Years, Working Condition 0.5 C @ 25 deg C, 80% DoD, 1 cycle per day
IP Rating	IP65
Cooling	Natural Cooling
Heating Power	230.4 W
Environment Protection Standard	RoHS

(1) Recommended Operating Temperature: 50°F - 86°F

(2) Recommended StorageTemperature: 50°F - 86°F

© All Rights Reserved  
Specifications subject to change without notice please  
ensure you are using the most recent update found at web:  
[usa.APsystem.com](http://usa.APsystem.com)

## APsystems America

8627 N Mopac Expy, Suite 150, Austin, TX 78759

Mail: [info.usa@APsystems.com](mailto:info.usa@APsystems.com)

Web: [usa.APsystems.com](http://usa.APsystems.com)