

S6-GC(25-60)K-US

Solis Three Phase Grid-Tied Inverters

Efficient

- Max. efficiency 98.8% (CEC efficiency 98.5%)
- String current up to 20A
- 3/4 MPPT design, supports multiple orientation system design
- Night time PID recovery function, increases overall system yield (optional)
- Wide voltage range and low startup voltage

Safe

- Type 4X, C5 Anti-Corrosion Level
- AFCI protection, proactively reduces fire risk
- Intelligent redundant fan-cooling
- Integrated module level rapid shutdown transmitter
- High quality components from globally recognized suppliers
- Integrated DC and AC disconnects

Smart

- Equipped with external power control interface, supporting zero output power control
- Intelligent string monitoring, smart I-V curve scan
- Supports RS485, Ethernet, WiFi, Cellular
- Scan to register on SolisCloud, supports remote upgrade and control

Economic

- > 1.5 DC/AC ratio
- Supports high power modules for lower installation costs
- Separable AC wiring box

Models:

S6-GC25K-US / S6-GC33K-US

S6-GC36K-US / S6-GC40K-US

S6-GC50K-US / S6-GC60K-US

Ordering: S6-GC(25-60)K-US

- APST (APS MLRSD Transmitter)
- RSS (Tigo MLRSD Transmitter)
- NEPT (NEP MLRSD Transmitter)



DATASHEET

S6-GC(25-60)K-US

Models	25K	33K	36K	40K	50K	60K
Input DC						
Max. input voltage				1000 V		
Rated voltage				720 V		
Start-up voltage				180 V		
MPPT voltage range				180-1000 V		
Max. input current			3*40 A		4*40 A	
Max. short circuit current			3*63 A		4*63 A	
MPPT number/Max. input strings number			3/6		4/8	
Output AC						
Rated output power	25 kW	33 kW	36 kW	40 kW	50 kW	60 kW
Max. apparent output power	27.5 kVA	36.3 kVA	39.6 kVA	44 kVA	55 kVA	66 kVA
Max. output power	27.5 kW	36.3 kW	39.6 kW	44 kW	55 kW	66 kW
Rated grid voltage				3Φ/PE, 480 V		
Rated grid frequency				60 Hz		
Max. output current	33.1 A	43.7 A	47.6 A	52.9 A	66.2 A	79.4 A
Power factor				>0.99 (0.8 leading - 0.8 lagging)		
THDi				<3%		
Efficiency						
Max. efficiency				98.8%		
CEC efficiency				98.5%		
Protection						
DC reverse-polarity protection				Yes		
Short circuit protection				Yes		
Output over current protection				Yes		
Surge protection				DC Type II / AC Type II		
Grid monitoring				Yes		
Anti-islanding protection				Yes		
Temperature protection				Yes		
Strings monitoring				Yes		
I/V Curve scanning				Yes		
Integrated AFCI (DC arc-fault circuit protection)				Yes		
Integrated PID recovery				Optional		
Integrated DC switch				Yes		
Integrated AC switch				Yes		
General Data						
Dimensions (W*H*D)				30.9*21.6*12.6 in (784*549*320 mm)		
Weight	96.3 lbs (43.7 kgs)		105.4 lbs (47.8 kgs)		108.7 lbs (49.3 kgs)	110.5 lbs (50.1 kgs)
Topology				Transformerless		
Self-consumption (night)				<1 W		
Relative humidity				0-100%		
Operating ambient temperature range				-13°F to 140°F (-25°C to 60°C)		
Ingress protection				TYPE 4X		
Cooling concept				Natural convection		
Max. operation altitude				13,120 ft (4000 m)		
Compliance				UL1741SB, UL1741SA, IEEE 1547-2018, UL1699B, UL1998, FCC Part15 ClassB, California Rule 21, Heco Rule 14H, NEC 690.12-2020, CAN/CSA C22.2107.1-1		
Features						
DC connection				MC4 connector		
AC connection				OT terminal (4 AWG to 3/0 AWG)		
Display				LCD		
Communication				Modbus RTU (Sunspec compliant), RS485, Optional: Cellular, Wi-Fi		