

FRONIUS PRIMO

/ SnapInverter
mounting system/ Wireless
monitoring/ Open data
communication/ Smart Grid
Ready/ Arc Fault Circuit
Interruption

The transformerless Fronius Primo is the ideal compact single-phase inverter for residential and small-scale commercial applications with power categories from 3.8 to 8.2 kW. In accordance with ESA rules for residential applications, the Fronius Primo can operate efficiently at a maximum input voltage of 600 V. And for increased efficiency and additional cost savings for commercial applications, the Fronius Primo can operate at the maximum input voltage of 1,000 V. Industry-leading features now come standard with the Fronius Primo, including: dual maximum power point tracking, arc fault protection, integrated wireless monitoring and SunSpec Modbus interfaces for seamless monitoring and datalogging via Fronius' online and mobile platform, Fronius Solar.web.

TECHNICAL DATA FRONIUS PRIMO

GENERAL DATA	FRONIUS PRIMO 3.8 - 8.2	FRONIUS PRIMO 10.0-15.0
Dimensions (width x height x depth)	16.9 x 24.7 x 8.1 in. / 42.9 x 62.7 x 20.6 cm	20.1 x 28.5 x 8.9 in. / 51.1 x 72.4 x 20.6 cm
Weight	47.4 lb. / 21.5 kg	82.5 lbs. / 37.4 kg
Degree of protection	NEMA 4X	
Night time consumption	< 1 W	
Inverter topology	Transformerless	
Cooling	Controlled forced ventilation, variable speed fan	
Installation	Indoor and outdoor installation	
Ambient operating temperature range	-40 to 131 F / -40 to 55 C	-40 to 140 F / -40 to 60 C
Permitted humidity	0 - 100 %	
DC connection terminals	2x DC+1, 2x DC+2 and 4x DC- screw terminals for solid: copper and aluminium stranded / fine stranded: copper and aluminium	4x DC+1, 2x DC+2 and 6x DC- screw terminals for copper (solid / stranded / fine stranded) or aluminium (solid / stranded)
AC connection terminals	Screw terminals 12 - 6 AWG	
Revenue Grade Metering	Optional (ANSI C12.1 accuracy)	
Certificates and compliance with standards	UL 1741-2010 Second Edition (incl. UL1741 Supplement SA 2016-09 for California Rule 21 and Hawaiian Electric Code Rule 14H), UL1998 (for functions: AFCI, RCMU and isolation monitoring), IEEE 1547-2003, IEEE 1547.1-2003, ANSI/IEEE C62.41, FCC Part 15 A & B, NEC 2017 Article 690, C22. 2 No. 107.1-16, UL1699B Issue 2 -2013, CSA TIL M-07 Issue 1 -2013	UL 1741-2010 Second Edition (incl. UL1741 Supplement SA 2016-09 for California Rule 21 and Hawaiian Electric Code Rule 14H), UL1998 (for functions: AFCI, RCMU and isolation monitoring), IEEE 1547-2003, IEEE 1547.1-2003, ANSI/IEEE C62.41, FCC Part 15 A & B, NEC 2017 Article 690, C22. 2 No. 107.1-16, UL1699B Issue 2 -2013, CSA TIL M-07 Issue 1 -2013

PROTECTIVE DEVICES	STANDARD WITH ALL PRIMO MODELS
AFCI	Yes
Ground Fault Protection with Isolation Monitor Interrupter	Yes
DC disconnect	Yes
DC reverse polarity protection	Yes

INTERFACES	AVAILABILITY	AVAILABLE WITH ALL FRONIUS PRIMO MODELS
USB (A socket)	Standard	Datalogging and inverter update via USB
2x RS422 (RJ45 socket)	Standard	Fronius Solar Net, interface protocol
Wi-Fi*/Ethernet/Serial/Datalogger and webserver	Optional	Wireless standard 802.11 b/g/n / Fronius Solar.web, SunSpec Modbus TCP, JSON / SunSpec Modbus RTU
6 inputs or 4 digital inputs/outputs	Optional	External relay controls

*The term Wi-Fi® is a registered trademark of the Wi-Fi Alliance.

TECHNICAL DATA FRONIUS PRIMO 3.8-1 TO 8.2-1

INPUT DATA	PRIMO 3.8-1	PRIMO 5.0-1	PRIMO 6.0-1	PRIMO 7.6-1	PRIMO 8.2-1
Max. permitted PV power (kWp)	5.7 kW	7.5 kW	9.0 kW	11.4 kW	12.3 kW
Max. usable input current (MPPT 1/MPPT 2)	18 A / 18 A	18 A / 18 A	18 A / 18 A	18 A / 18 A	18 A / 18 A
Total max. DC current	36 A				
Max. admissible input current (MPPT 1/MPPT 2)	27 A				
Operating voltage range	80 V - 1,000 V				
Max. input voltage	1,000 V				
Nominal input voltage	410 V	420 V	420 V	420 V	420 V
Admissible conductor size DC	AWG 14 - AWG 6				
MPP voltage range	200 - 800 V	240 - 800 V	240 - 800 V	250 - 800 V	270 - 800 V
Number of MPPT	2				

OUTPUT DATA	PRIMO 3.8-1	PRIMO 5.0-1	PRIMO 6.0-1	PRIMO 7.6-1	PRIMO 8.2-1
Max. output power	240 V	3,800 W	5,000 W	6,000 W	7,600 W
	208 V	3,800 W	5,000 W	6,000 W	7,900 W
Max. output fault current / Duration	240 V	584 A Peak / 154 ms	584 A Peak / 154 ms	584 A Peak / 154 ms	584 A Peak / 154 ms
Max. continuous output current	240 V	15.8 A	20.8 A	25.0 A	31.7 A
	208 V	18.3 A	24.0 A	28.8 A	36.5 A
Recommended OCPD/AC breaker size	240 V	20 A	30 A	35 A	40 A
	208 V	25 A	30 A	40 A	50 A
Max. efficiency (Lite version)	97.9 %				
CEC efficiency (Lite version)	240 V	95.5 %	96.5 %	96.5 %	97.0 %
Admissible conductor size AC	AWG 14 - AWG 6				
Grid connection	208 / 240 V				
Frequency	60 Hz				
Total harmonic distortion	< 5.0 %				
Power factor (cos $\varphi_{ac,r}$)	0.85 - 1 ind./cap				

TECHNICAL DATA FRONIUS PRIMO 10.0-1 TO 15.0-1

INPUT DATA	PRIMO 10.0-1	PRIMO 11.4-1	PRIMO 12.5-1	PRIMO 15.0-1
Max. permitted PV power (kWp)	15.00 kW	17.10 kW	18.75 kW	22.50 kW
Max. usable input current (MPPT 1/MPPT 2)	33.0 A / 18.0 A			
Total max. DC current	51 A			
Max. admissible input current (MPPT 1/MPPT 2)	49.5 A / 27.0 A			
Operating voltage range	80 V - 1,000 V			
Max. input voltage	1,000 V			
Nominal input voltage	655 V	660 V	665 V	680 V
Admissible conductor size DC	AWG 14 - AWG 6 copper direct, AWG 6 aluminum direct, AWG 4 - AWG 2 copper or aluminum with optional input combiner			
MPP Voltage Range	220 - 800 V	240 - 800 V	260 - 800 V	320 - 800 V
Number of MPPT	2			

OUTPUT DATA	PRIMO 10.0-1	PRIMO 11.4-1	PRIMO 12.5-1	PRIMO 15.0-1
Max. output power	240 V	9,995 W	11,400 W	12,500 W
	208 V	9,995 W	11,400 W	12,500 W
Max. output fault current / Duration	240 V	916 A Peak / 6.46 ms	916 A Peak / 6.46 ms	916 A Peak / 6.46 ms
Max. continuous output current	240 V	41.6 A	47.5 A	52.1 A
	208 V	48.1 A	54.8 A	60.1 A
Recommended OCPD/AC breaker size	240 V	60 A	60 A	70 A
	208 V	60 A	70 A	80 A
Max. efficiency (Lite version)	97.9 %			
CEC efficiency (Live version)	240 V	96.5 %	96.5 %	96.5 %
Admissible conductor size AC	AWG 10 - AWG 2 copper (solid / stranded / fine stranded) , AWG 6 - AWG 2 copper (solid / stranded)			
Grid connection	208 / 240 V			
Frequency	60 Hz			
Total harmonic distortion	< 2.5 %			
Power factor (cos $\varphi_{ac,r}$)	0-1 ind./cap.			