



Included



Optional



Blue Smart IP65 Charger 120V	6 12 V: 1.1 A	12V: 5 7 10 15 25A	24V: 5 8 13A
Input voltage	100 - 250VAC		100-130 VAC
Efficiency	82%	94%	95%
Standby power consumption	<0.5W		0.5W
Minimum battery voltage	Starts charging from down to 0V		
Charge voltage 'absorption'	Normal: 7.2V 14.4V High: 7.35V 14.7V Li-ion: 7.1V 14.2V	Normal: 14.4V High: 14.7V Li-ion: 14.2V	Normal: 28.8V High: 29.4V Li-ion: 28.4V
Charge voltage 'float'	Normal: 6.9V 13.8V High: 6.9V 13.8V Li-ion: Disabled	Normal: 13.8V High: 13.8V Li-ion: 13.5V	Normal: 27.6V High: 27.6V Li-ion: 27.0V
Charge voltage 'storage'	Normal: 6.6V 13.2V High: 6.6V 13.2V Li-ion: 6.75V 13.5V	Normal: 13.2V High: 13.2V Li-ion: 13.5V	Normal: 26.4V High: 26.4V Li-ion: 27.0V
Charge current	1.1A	5 7 10 15 25 A	5 8 13 A
Charge current in low current mode	0.5A	2 2 3 4 10 A	2 3 4 A
Temperature compensation (lead-acid batteries only)	8mV/°C 16mV/°C	16 mV/°C (9mV/°F)	32 mV/°C (18mV/°F)
Can be used as power supply	Yes		
Back current drain	0.1Ah/month (0.14mA)	0.7Ah/month (1mA)	
Protection	Reverse polarity Output short circuit Over temperature		
Operating temperature range	-30 to +50°C (full rated output up to 30°C) -22 to +122°F (full rated output up to 90°F)	-40 to +60°C (full rated output up to 30°C) -40 to +140°F (full rated output up to 90°F)	
Maximum humidity (non condensing)	95%		
ENCLOSURE			
Battery-connection	Black and red cable of 1.5 meter (4.9 feet)		
120 V AC-connection	1.8 meter cable (5.9 feet) with US NEMA 1-15 plug		
Protection category	IP65 (splash proof, dust proof and ignition protected)		
Weight	0.4 kg (0.9lbs)	12/25 & 24/13 models: 1.9kg (4.2lbs) Other models: 0.9kg (2.0lbs)	
Dimensions (h x w x d)	36 x 64 x 153 mm	12/5 & 12/7: 47x95x190mm (1.9x3.7x7.5 inch)	24/5: 47x95x190mm (1.9x3.7x7.5 inch)
		12/10 & 12/15: 60x105x190mm (2.4x4.1x7.5 inch) 12/25: 75x140x240mm (3.0x5.5x9.4 inch)	24/8: 60x105x190mm (2.4x4.1x7.5 inch) 24/13: 75x140x240mm (3.0x5.5x9.4 inch)
STANDARDS			
Safety	EN 60335-1, 60335-2-29	UL 1236, CSA C22.2, EN 60335-1, 60335-2-29	
Emission	EN 55014-1, EN 61000-6-3, EN 61000-3-2		
Immunity	EN 55014-2, EN 61000-6-1, EN 61000-6-2, EN 61000-3-3		



victron energy
BLUE POWER

www.victronenergy.com
Customer support: sales@victronenergy.com



Blue Smart Charger

IP65 The professional's choice



Energy. Anytime. Anywhere.


- Water, dust and chemical resistant
- Seven step smart charge algorithm
- Recovery of fully discharged 'dead' batteries
- Automatic power supply function
- Severe cold performance: down to -30°C
- Several other battery life enhancing features
- Low power mode to charge smaller batteries
- **Li-ion** battery mode
- Setup and configure, readout of voltage and current by **Bluetooth Smart**

Ultra high efficiency “green” battery charger

With up to 95% efficiency, these chargers generate up to four times less heat when compared to the industry standard. And once the battery is fully charged, power consumption reduces to 0,5 Watt, some five to ten times better than the industry standard.

Durable, safe and silent

- Low thermal stress on the electronic components.
- Protection against ingress of dust, water and chemicals.
- Protection against overheating: the output current will reduce as temperature increases up to 60°C, but the charger will not fail.
- The chargers are totally silent: no cooling fan or any other moving parts.



Reconditioning

A lead-acid battery that has been insufficiently charged or has been left discharged during days or weeks will deteriorate due to sulfation. If caught in time, sulfation can sometimes be partially reversed by charging the battery with low current up to a higher voltage.

Recovery function for fully discharged batteries


Most reverse polarity protected chargers will not recognize, and therefore not recharge a battery which has been discharged to zero or nearly zero Volts. The **Blue Smart IP65 Charger** however will attempt to recharge a fully discharged battery with low current and resume normal charging once sufficient voltage has developed across the battery terminals.

The VictronConnect app

Setup, readout and configure your **Blue Smart IP65 Charger** via your smartphone.

You can display the status of your charger and battery and even control the functions of your charger using the VictronConnect app. On your screen the readout of voltage and current is default available.

Download your app for iOS and Android here at <https://www.victronenergy.com/live/victronconnect:start>



Storage mode: less corrosion of the positive plates

Even the lower float charge voltage that follows the absorption period will cause grid corrosion. It is therefore essential to reduce the charge voltage even further when the battery remains connected to the charger during more than 48 hours.

Temperature compensated charging

The optimal charge voltage of a lead-acid battery varies inversely with temperature. The **Blue Smart IP65 Charger** measures ambient temperature during the test phase and compensates for temperature during the charge process. The temperature is measured again when the charger is in low current mode during float or storage. Special settings for a cold or hot environment are therefore not needed.

Li-ion battery mode

The **Blue Smart IP65 Charger** uses a specific charging algorithm for Li-ion (LiFePO₄) batteries, with automatic Li-ion under voltage protection reset.



IP65 - Charger Guide

Blue Smart IP65 Charger

Battery size Ah Your IP65 Charger »	7 A 20 - 70 Ah	12V 10 A 30 - 100 Ah	15 A 50 - 150 Ah	24V 8 A 30 - 80 Ah	CLASSIC	MODERN	AGM	GEL	Li-ion	LiFePO4
	12/7	12/10	12/15	24/8						
Motorcycle	OK	OK	OK	OK						
Motorcycle	OK	OK	OK	OK						
Car	OK	OK	OK	OK						
Car	OK	OK	OK	OK						
Caravan	OK	OK	OK	OK						
Truck	OK	OK	OK	OK						
Sailboat	OK	OK	OK	OK						

Recommended

This is the best charger for this type of battery. The battery will be charged in the most efficient way.

OK

This charger can be used for this battery. It is possible that it takes longer to charge the battery than using a recommended charger.