

# NPA10S-12I

## Monocrystalline Module

30 Cell


Monocrystalline Module

10W

Power Output

21.3%

Maximum Efficiency



### 9BB Cell Technology

- 21.3% max efficiency with 9BB Multibusbar technology enabling maximum BOS savings
- Multibusbar M6 Mono Half-Cell uplifted with PERC technology to guarantee higher output power and maximum module efficiency



### Extreme Weather Simulation

- Withstood 1.375" diameter hailstones falling at terminal velocity
- Rugged design with hail/snow tolerance up to 5400 Pa positive load and high wind tolerance up to 2400 Pa negative load



### Efficient Sorting Process

- Identify and mitigate against damaged/color-deviating/chipped cells
- Standardized cell efficiency testing to ensure optimal PV output




### Highly Reliable

- Robust encapsulation and diffusion barriers provide long term protection against PID damage
- Adaptability to temperatures below 0°F to 149°F

Positive mechanical load >5400Pa  
 Positive Power Tolerance 0~+5W  
 Warranty 25-year Linear Power Warranty

### Performance Warranty



## ELECTRICAL CHARACTERISTICS


Type	NPA10S-12I
Power Output(W)	10W
Voltage MPP Vmp(V)	17.37V
Current MPP Imp(A)	0.69A
Voltage Open Circuit Voc(V)	20.04V
Short Circuit Current Isc(A)	0.73A
Temperature Coefficient Of Voc	-[80±10]mV/°C
Temperature Coefficient Of Isc	[0.065±0.015]%/°C
Temperature Coefficient Of Power	-[0.5±0.05]%/°C
NOCT (Air 20°C; Sun 0.8kW/m <sup>2</sup> wind 1m/s)	47±2°C

STC: 1000W/m<sup>2</sup> Irradiance, 25°C module temperature, AM1.5g spectrum according to EN 60904-3



## MECHANICAL CHARACTERISTICS

Cells	Monocrystalline Silicon
Solar Cells Grade	Class A High Efficiency
Module Dimension(in./mm)	15.35[390]x7.68[195]x0.71[18]
Weight(lbs/kg)	2.06[0.93]
Packing Information(in./mm)	16.93[430]x9.25[235]x8.86[225]/(10pcs/ctn)

## I-V CURVES (Irradiance: AM1.5, 1kw/m<sup>2</sup>)



\*Specifications subject to technical changes and tests.  
NEWPOWA reserves the right of final interpretation.



702-628-7600



sales@newpowa.com



www.newpowa.com



3633 Inland Empire Blvd, Ste 600, Ontario, CA 91764