

NEOVOLTA™



# Hybrid Inverter

## NV7600

Designed and Engineered in  
California since 2018

**Compact Design**  
**On Grid and Off Grid**  
**DC and AC Solar**  
**Generator Ready**  
**Stackable**



Type Approved  
Safety  
Regular Production  
Surveillance  
[www.tuv.com](http://www.tuv.com)  
ID 11127848



800.364.5464

NEOVOLTA.COM

### PV String Input Data

Max. PV Input Power* (W)	11,400**
Max. PV Input Voltage (Voc)	500
Startup Voltage (Vmp)	125
MPPT Voltage Range (Vmp)	150-425
Rated PV Input Voltage	370
Max. Operation PV Input Current (A) @ MPPT	26 +26
Max. Input Short-Circuit Current (A) @ MPPT	44+44
MPPT   Strings per MPPT	2   2+2

\*Max. PV Input Voltage of 500Voc shall be calculated at coldest operating temperature of installation locations.

\*\* Inverter will self-limit to 11,400W of max combined solar input.

### AC Input/Output Data

Rated AC Output (W/VA)	7,600/8360
Max. AC Solar or Generator Input	8,360
Rated AC Input/Output (A)	31.7
Max. AC Input/Output (A)	34.8
Max. Continuous AC Passthrough (grid to load) (A)	50
Peak Power (off-grid) (W)	2 times rated power (15,200W); 10s
Power Factor Adjustment Range	0.9 - 1.0
Rated Input/Output Voltage   Voltage Range (V)	120/240; 208/3-Phase
Rated Input/Output Frequency   Frequency Range (Hz)	60   55-65
Grid Connection Form	2L + N + PE
Total Current Harmonic Distortion (THDi)	<3% (of nominal power)
Max. Parallel for on-grid and off-grid*	4(pcs) 120/240Vac   3(pcs) 120/208Vac

\*This is for inverter paralleling ONLY. NV7600 w/ NVPLUS is UL9540 listed for (4) inverters w/ (5) batteries

### Battery Input Data (DC)

Battery Type (Compatible)	Lithium Iron Phosphate (LiFePO4)
Battery Voltage Range (V)	4-60
Max. Charging Current (A)	190
Max. Discharging Current (A)	190
Charging Strategy for Li-ion Battery	Self-Adoption BMS
Number of Battery Input	1 (2 wires; positive and negative)

### Equipment

Integrated

**Protection:** DC Polarity Reverse Connection, AC Output Overcurrent, Thermal, AC Output Overvoltage, AC Output Short Circuit, Overvoltage Load Drop, Surge

**Monitoring:** DC Component, Ground Fault Current, Power Network, Island Protection, Earth Fault Detection, DC Input Switch, DC Terminal Insulation Impedance, Residual Current (RCD) Detection, Arc Fault Circuit Interrupter (optional)

Surge Protection	Type II (DC), TYPE II (AC)
Communication Interface	RS485   RS232   CAN
Monitor Mode	GRPS   WiFi   Bluetooth   4G   LAN (optional)

### General Data

Operating Temperature	-40F - 140F
Humidity Limit (%)	up to 100
Max. Elevation	2000m/6561ft (10% derating at 3000m/9842ft)
Noise (dB)	<30
IP Rating	TYPE 3R
Typology	Non-Isolated
Overvoltage Category	OVC II (DC), OVC III (AC)
Dimensions (W x H x D)   Weight (lbs)	16.5" x 26.4 x 9.2"   66
Cooling	Intelligent Air Cooling
Max. Efficiency (%)	97.6
MPPT Efficiency (%)	>99.0
Warranty	15 years
Grid Regulation   Certifications	IEEE1547.1 SRD V2.0   UL1741 CRD   UL1741 SB   UL1699B   CEC
Load Start Capability*	80A

\*Load start capability may vary

Disclaimer: The information provided herein is correct to the best of NeoVolta's knowledge, is presented in good faith and believed to be correct at the time of printing. No liability for any errors, facts or opinions is accepted. In no event will NeoVolta be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this specification sheet or the products to which the information refers. All weights and measures shown are best approximations.