



samlexamerica®

1500W



DC-AC Inverter Modified Sine Wave

Model
SAM-1500-12
12 VDC
115 VAC

Design Features

- Compact design
- Load controlled cooling fan
- Low battery input alarm
- Universal protection circuit: thermal, battery, overload, short circuit, earth fault
- Soft start technology
- Cool surface technology
- Low interference technology

2 YEAR WARRANTY



MODEL NO.		SAM-1500-12
INPUT	BATTERY SYSTEM VOLTAGE	12 VDC
	NOMINAL INPUT VOLTAGE	12.5 VDC
	INPUT VOLTAGE RANGE	10.5 VDC to 15.0 (± 0.5) VDC
	INPUT CURRENT AT CONTINUOUS POWER	150A
	INPUT CURRENT AT NO LOAD	0.65A to 0.75A
OUTPUT	OUTPUT VOLTAGE WAVE FORM	Modified Sine Wave
	OUTPUT VOLTAGE	115 VAC
	OUTPUT VOLTAGE REGULATION	+ 10% / - 0%
	OUTPUT FREQUENCY	60 Hz ± 5%
	OUTPUT POWER, CONTINUOUS (RESISTIVE LOAD)	1500W
	OUTPUT POWER, SURGE (< 1 SEC, RESISTIVE LOAD)	3000W
	PEAK EFFICIENCY (AT 50% OF CONTINUOUS POWER)	90%
PROTECTIONS	USB CHARGING PORT	Not available
	LOW INPUT VOLTAGE ALARM	Yes (10.8 VDC ± 0.3 VDC)
	LOW INPUT VOLTAGE SHUTDOWN	10.5 VDC ± 0.5 VDC
	HIGH INPUT VOLTAGE SHUTDOWN	Yes. (> 15.5 VDC ± 0.2 VDC)
	OVERLOAD & GROUND FAULT SHUT DOWN	Yes (Latches in shutdown condition. Manual reset by switching OFF and switching ON the ON /OFF Switch)
	OVER TEMPERATURE SHUTDOWN	Internal Hot Spot 88°C to 115°C. Auto-reset when cools down by 10°C to 15°C.
	COOLING FAN, LOAD CONTROLLED, ON AT	90 to 110W
	LEAKAGE PROTECTION	Yes (Shutdown)
	INPUT FUSE, 32 V	240A (8 x 30A)
CONNECTIONS	INPUT CONNECTION	Nut & Bolt, M9
	AC OUTPUT - No OF NEMA5-15R RECEPTACLES	2
	REMOTE CONTROL PORT	Yes
GENERAL	OPERATING TEMPERATURE RANGE	0°C to 25°C / 32°F to 77°F at 100% loading; 26°C to 35°C / 78.8°F to 95°F at 80% loading
	OPERATING HUMIDITY	< 80%
	NEUTRAL TO CHASSIS BONDING	No. Neutral is floating
	DIMENSIONS, MM (W x D x H)	202 x 283 x 84
	DIMENSIONS, INCHES (W x D x H)	7.95 x 11.14 x 3.3
	WEIGHT, KG	3.2
	WEIGHT, LB	7.1

NOTE: Specifications are subject to change without notice

12002-SAM-1500-12-0814