

Three Phase Inverter with Synergy Technology

For the 208V Grid for North America

SE50KUS



Powered by unique pre-commissioning process for rapid system installation

- / Pre-commissioning feature for automated validation of system components and wiring during the site installation process and prior to grid connection
- / Easy 2-person installation with lightweight, modular design (each inverter consists of 3 Synergy units and one Synergy Manager)
- / Independent operation of each Synergy unit enables higher uptime and easy serviceability
- / Built-in thermal sensors detect faulty wiring ensuring enhanced protection and safety
- / Built-in arc fault protection and rapid shutdown
- / Built-in PID mitigation for maximized system performance
- / Monitored* and field-replaceable surge protection devices, to better withstand surges caused by lightning or other events
- / Built-in module-level monitoring with Ethernet or cellular communication for full system visibility

*Applicable only for DC and AC SPDs

/ Three Phase Inverter with Synergy Technology

For the 208V Grid for North America

SE50KUS

Applicable to inverter with Part Numbers	SExxK-US02Ixxxx	
	SE50KUS	
OUTPUT		
Rated AC Active Output Power	50000	W
Maximum AC Apparent Output Power	50000	VA
AC Output Line Connections	3W + PE, 4W + PE	
Supported Grids	WYE: TN-C, TN-S, TN-C-S, TT, IT; Delta: IT	
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-N)	105-120-132.5	Vac
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-L)	183-208-229	Vac
AC Frequency Min-Nom-Max ⁽¹⁾	59.5 - 60 - 60.5	Hz
Maximum Continuous Output Current (per Phase, PF=1)	139.5	Aac
GFDI Threshold	1	A
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes	
Total Harmonic Distortion	≤ 3	%
Power Factor Range	+/-0.2 to 1	
INPUT		
Maximum DC Power (Module STC) Inverter / Synergy Unit	75000 / 25000	W
Transformer-less, Ungrounded	Yes	
Maximum Input Voltage DC+ to DC-	600	Vdc
Operating Voltage Range	370 - 600	Vdc
Maximum Input Current	3 x 46.5	Adc
Reverse-Polarity Protection	Yes	
Ground-Fault Isolation Detection	167kΩ sensitivity per Synergy Unit ⁽²⁾	
CEC Weighted Efficiency	97	%
Nighttime Power Consumption	< 12	W
ADDITIONAL FEATURES		
Supported Communication Interfaces ⁽³⁾	2 x RS485, Ethernet, Wi-Fi (optional), Cellular (optional)	
Smart Energy Management	Export Limitation	
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi access point for local connection	
Arc Fault Protection	Built-in, User Configurable (According to UL1699B)	
Photovoltaic Rapid Shutdown System	NEC 2014, 2017 and 2020, Built-in	
PID Rectifier	Nighttime, built-in	
RS485 Surge Protection (ports 1+2)	Type II, field replaceable, integrated	
AC, DC Surge Protection	Type II, field replaceable, integrated	
DC Fuses (Single Pole)	25A, integrated	
DC SAFETY SWITCH		
DC Disconnect	Built-in	
STANDARD COMPLIANCE		
Safety	UL1699B, UL1741, UL1741 SA, UL1998, CSA C22.2#107.1, Canadian AFCI according to T.I.L. M-07	
Grid Connection Standards	IEEE 1547, Rule 21, Rule 14 (H1)	
Emissions	FCC part 15 class A	

(1) For other regional settings please contact SolarEdge support

(2) Where permitted by local regulations

(3) For specifications of the optional communication options, visit <https://www.solaredge.com/products/communication> or the Resource Library webpage: <https://www.solaredge.com/downloads#>, to download the relevant product datasheet

/ Three Phase Inverter with Synergy Technology

For the 208V Grid for North America

SE50KUS

Applicable to inverter with Part Numbers	SExxK-US02Ixxxx	
	SE50KUS	
INSTALLATION SPECIFICATIONS		
Number of Synergy Units per Inverter	3	
AC Max Conduit Size	2 ½"	in
Max AWG Line / PE	4/0 / 1/0	
DC Max Conduit Size	1 x 3"; 2 x 2"	in
DC Input Inverter / Synergy Unit	12 / 4 pairs; 6-12 AWG	
Dimensions (H x W x D)	Synergy Unit: 22 x 12.9 x 10.75 / 558 x 328 x 273 Synergy Manager: 14.17 x 22.4 x 11.6 / 360 x 560 x 295	in / mm
Weight	Synergy Unit: 70.4 / 32 Synergy Manager: 39.6 / 18	lb / kg
Operating Temperature Range	-40 to +140 / -40 to +60 ⁽⁴⁾	°F / °C
Cooling	Fan (user replaceable)	
Noise	< 67	dBA
Protection Rating	NEMA 3R	
Mounting	Brackets provided	

(4) For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>