



# Microinverter Datasheet

- HMS-700-2T-NA**
- HMS-800-2T-NA**
- HMS-900-2T-NA**
- HMS-1000-2T-NA**

## Description

Hoymiles new microinverter HMS-1000 series are suitable for high-powered solar panels, which rank among the highest for 2-in-1 microinverters.

Each microinverter can connect up to 2 panels, with independent MPPT and monitoring maximizing the power production of your installation. With a maximum DC voltage of 65 volts, Hoymiles microinverter is a PV Rapid Shutdown Equipment and conforms with NEC-2017 and NEC-2020 Article 690.12 and CEC-2021 Sec 64-218.

The new Sub-1G wireless solution enables more stable communication with Hoymiles gateway DTU.

## Features

- |   |   |
|---|---|
| <p><b>01</b> High-powered microinverter for 2-in-1 series with superior performance</p>           | <p><b>04</b> Independent MPPT and monitoring ensure greater energy harvest and easier maintenance</p>       |
| <p><b>02</b> Safer for rooftop solar stations with PV rapid shutdown compliance</p>               | <p><b>05</b> 2-in-1 design enables faster installation</p>  |
| <p><b>03</b> With Reactive Power Control, compliant with UL 1741, IEEE 1547, UL 1741 SB, etc.</p> | <p><b>06</b> Sub-1G wireless solution allows stable communication in commercial and industrial settings</p> |

# Technical Specifications

Model	HMS-700-2T-NA		HMS-800-2T-NA		HMS-900-2T-NA		HMS-1000-2T-NA	
<b>Input Data(DC)</b>								
Commonly used module power (W)	280 to 470+		320 to 540+		360 to 600+		400 to 670+	
Maximum input voltage (V)	60		65		65		65	
MPPT voltage range (V)					16-60			
Start-up voltage (V)					22			
Maximum input current (A)	2 × 13		2 × 14		2 × 15		2 × 16	
Maximum input short circuit current (A)	2 × 20		2 × 25		2 × 25		2 × 25	
Number of MPPTs					2			
Number of Inputs per MPPT					1			
<b>Output Data(AC)</b>								
Peak output power (VA)	700		800		900		1000	
Maximum continuous output power (VA)	638		720		820		958	
Maximum continuous output current (A)	2.66	3.07	3	3.46	3.42	3.94	3.99	4.61
Nominal output voltage/range (V) <sup>1</sup>	240/211-264	208/183-228	240/211-264	208/183-228	240/211-264	208/183-228	240/211-264	208/183-228
Nominal frequency/range (Hz) <sup>1</sup>					60/55-65			
Power factor (adjustable)					> 0.99 default 0.8 leading ... 0.8 lagging			
Total harmonic distortion					< 3%			
Maximum units per 10 AWG branch <sup>2</sup>	9	7	8	6	7	6	6	5
Maximum units per 12 AWG branch <sup>2</sup>	6	5	5	4	4	4	4	3
<b>Efficiency</b>								
CEC peak efficiency	96.70%		96.70%		96.50%		96.50%	
Nominal MPPT efficiency					99.80%			
Night power consumption (mW)					< 50			
<b>Mechanical Data</b>								
Ambient temperature range (°C)					-40 to +65			
Dimensions (W × H × D [mm])					261 × 180 × 35.1			
Weight (kg)					3.2			
Enclosure rating					Outdoor-IP67 (NEMA6)			
Cooling					Natural convection-No fans			
<b>Features</b>								
Communication					Sub-1G			
Type of isolation					Galvanically Isolated HF Transformer			
Monitoring					Hoymiles S-Miles Cloud <sup>3</sup>			
Compliance					UL 1741, IEEE 1547, UL 1741 SB (Pending), CSA C22.2 No. 107.1-16 FCC 15B, FCC 15C			
PV Rapid Shutdown					Conforms with NEC-2017 and NEC-2020 Article 690.12 and CEC-2021 Sec 64-218 Rapid Shutdown of PV Systems.			

\*1 Nominal voltage/frequency range can vary depending on local requirements.

\*2 Refer to local requirements for exact number of microinverters per branch.

\*3 Hoymiles Monitoring System