



Safety switch, general duty, fusible, 2 pole, 3 wire, 240VAC, 200A, Type 3R, bolt on hub prov, with neutral

D224NRB

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Single Throw Safety Switch	
Duty Rating	General duty	
Device Application	Residential	
Disconnect Type	Fusible disconnect switch	
Factory Installed Neutral	Neutral (factory installed)	
Number of Poles	2	
Current Rating	200 A	
Voltage Rating	240 V AC	
Enclosure Rating NEMA	NEMA 3R	
Motor power hp	15 hp at 240 V AC 60 Hz for 1 phase motors 25 hp at 240 V AC 60 Hz for 3 phase motors 60 hp at 240 V AC 60 Hz for 3 phase motors	

Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R	
Fuse type	H, K or R	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 6250 kcmil aluminium/copper	
Tightening torque	275 lbf.in (31.07 N.m) (AWG 6250 kcmil)	
Depth	8.5 in (215.9 mm)	
Width	19 in (482.6 mm)	
Height	29.25 in (742.95 mm)	
Net Weight	53.51 lb(US) (24.27 kg)	

Environment

Certifications UL listed file E2875

Ordering and shipping details

Category	US1DE1A00106	
Discount Schedule	DE1A	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

GTIN	785901460763	
Returnability	Yes	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.50 in (21.590 cm)	
Package 1 Width	19.50 in (49.530 cm)	
Package 1 Length	30.50 in (77.470 cm)	
Package 1 Weight	42.631 lb(US) (19.337 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	15	
Package 2 Height	40.00 in (101.600 cm)	
Package 2 Width	40.00 in (101.600 cm)	
Package 2 Length	48.00 in (121.920 cm)	
Package 2 Weight	647.000 lb(US) (293.474 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	180
Environmental Disclosure	Product Environmental Profile

Use Better


Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration


Dimensions



INHEN MOUNTING THESE SMITCHES, ALLOW 4 50 (100) MIN CLEARANCE BETHERE INCLOSUMES FOR OPPOINTS OF SIDE HANGED BOOK TO FOR ARBITATIVE DEFOUCES HAVE PROMISSING FOR MARKAME 3 OF SING SOCIETION HAS ALL DIMENSIONS ARE APPROXIMANTE. REPER TO TECHNICAL DRAWNINGS AND DOCUMENTAL **Technical Illustration**

Wiring diagram

FUSIBLE



D224NRB