



Safety switch, general duty, non fusible, 3 pole, 3 wire, 240VAC, 200A, Type 3R with bolt on hub prov

DU324RB

Product availability: Stock - Normally stocked in distribution facility

#### Main

Product	Single Throw Safety Switch	
Duty Rating	General duty	
Device Application	Residential	
Disconnect Type	Non-fusible disconnect switch	
Factory Installed Neutral	None	
Number of Poles	3	
Current Rating	200 A	
Voltage Rating	240 V AC	
Enclosure Rating NEMA	NEMA 3R	
Motor power hp	15 hp at 240 V AC 60 Hz for 1 phase motors 60 hp at 240 V AC 60 Hz for 3 phase motors	

### Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 6250 kcmil aluminium/copper	
Tightening torque	275 lbf.in (31.07 N.m) (AWG 6250 kcmil)	
Depth	8.25 in (209.55 mm)	
Width	19 in (482.6 mm)	
Height	29 in (736.6 mm)	
Net Weight	53.00 lb(US) (24.04 kg)	

#### **Environment**

Certifications UL listed file E2875

### Ordering and shipping details

Category	US1DE1A00106	
Discount Schedule	DE1A	
GTIN	785901491880	
Returnability	Yes	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin US

## **Packing Units**

_		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.70 in (22.098 cm)	
Package 1 Width	19.40 in (49.276 cm)	
Package 1 Length	30.80 in (78.232 cm)	
Package 1 Weight	44.851 lb(US) (20.344 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	15	
Package 2 Height	46.00 in (116.84 cm)	
Package 2 Width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	
Package 2 Weight	652.00004 lb(US) (295.742 kg)	

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg CO2 eq, Total Life cycle)	206	
Environmental Disclosure	Product Environmental Profile	

#### **Use Better**


Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

#### **Technical Illustration**


#### **Dimensions**



**Technical Illustration** 

Wiring diagram

# **NOT FUSIBLE**



DU324RB

Image of product / Alternate images

#### **Alternative**

