



Mini circuit breaker, Homeline, 35A, 2 pole, 120/240VAC, 10kA AIR, standard type, plug in, UL

HOM235

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	35 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	1 x AWG 8AWG 2 (aluminium/copper)

Complementary

· · · · · · · · · · · · · · · · · · ·	-	
Tightening torque	40.7 lbf.in (4.6 N.m) (AWG 8AWG 2)	
Height	3.13 in (79.50 mm)	
Width	2 in (50.8 mm)	
Depth	2.98 in (75.69 mm)	

Environment

Ambient Air Temperature for 104 °F (40 °C) Operation

Ordering and shipping details

Category	US1DE3D00046
Discount Schedule	DE3D
GTIN	785901065494
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1 PCE

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of Units in Package 1	1	
Package 1 Height	3.10 in (7.87 cm)	
Package 1 Width	2.00 in (5.08 cm)	
Package 1 Length	3.20 in (8.13 cm)	
Package 1 Weight	11.20 oz (317.52 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	5	
Package 2 Height	3.20 in (8.128 cm)	
Package 2 Width	2.60 in (6.604 cm)	
Package 2 Length	10.20 in (25.908 cm)	
Package 2 Weight	3.609 lb(US) (1.637 kg)	
Unit Type of Package 3	CAR	
Number of Units in Package 3	50	
Package 3 Height	10.50 in (26.67 cm)	
Package 3 Width	7.10 in (18.034 cm)	
Package 3 Length	16.70 in (42.418 cm)	
Package 3 Weight	36.500 lb(US) (16.556 kg)	

Contractual warranty

Warranty Lifetime



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	23	

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions




Image of product / Alternate images

Alternative

Technical Benefits Thermal Magnetic Breaker



Miniature circuit breaker rated at 35A



Protects against overloads and short-circuits



Product characteristics conformity is certified by the Underwriters Laboratories (UL)





The current capacity that this circuit breaker is able to interrupt before breaking is 10kA



For residential/ commercial use to protect entire branch circuits



Compatible with Homeline electrical panel and CSEDs with 2 spaces



5