



#### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR and Switching Duty rated
Electrical Connection	Pressure plate

#### Complementary

Interrupt Rating	10 KA 120/240 V AC 10 kA 120 V AC
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.0 in (76 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Net Weight	0.300 lb(US) (0.136 kg)

#### Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

#### Ordering and shipping details





Category	US1DE2A00004
Discount Schedule	DE2A
GTIN	785901400066
Returnability	Yes
Country of origin	IE

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.7 in (1.8 cm)
Package 1 Width	3.03 in (7.7 cm)
Package 1 Length	3.3 in (8.4 cm)
Package 1 Weight	4.3 oz (123 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.2 in (8.2 cm)
Package 2 Width	3.3 in (8.4 cm)

Package 2 Length	7.6 in (19.4 cm)
Package 2 Weight	2.820 lb(US) (1.279 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	6.9 in (17.6 cm)
Package 3 Width	8.1 in (20.6 cm)
Package 3 Length	17.2 in (43.7 cm)
Package 3 Weight	28.739 lb(US) (13.036 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------